

CP- SNP-2020MPL10D

2 MP Full HD Network Mobile PTZ Camera



Main Features

- 1/2.8" Progressive Scan CMOS Image Sensor
- 2MP Image Quality
- Powerful 20x Optical Zoom
- WDR, 3D DNR, Day/Night(ICR), BLC, AGC, AWB
- Pan range: 360° endless, speed up to 60°/s
- Up to 128 Presets
- IR Distance up to 100 Mtr., IP66
- Supports H.265/H.264 dual-stream
- Anti-vibration design



*Product casing and specifications are subject to change without prior notice

CP- SNP-2020MPL10D


2 MP Full HD Network Mobile PTZ Camera

Feature

Image Sensor
Effective Pixels
S/N Ratio
Minimum Illumination
Focal Length
Focus Control
White Balance
Angle of View
Electronic Shutter
AGC control
Back Light Compensation
Optical Zoom
Pan Travel
Tilt Travel
Presets
Preset Speed
Special Features
Day/Night: IR Cut Filter
Video Compression
Video Streaming
Audio Compression
Protocols
Max Remote Users
Memory Slot
Operating Temperature
Weather Proof Standard
Weight
Power Source

Specification

1/2.8" Progressive CMOS
1920(H) x 1080(V), 2 Megapixels
More than 52dB
Color: 0.05Lux @ (F1.6, AGC ON) Black & white: 0.01Lux @ (F1.6, AGC ON)
4.7mm - 94mm
Auto focus / Onefocus / Manual focus
Auto
H: 61.4°~2.9 degrees (wide angle- telephoto)
1/1second ~ 1/30,000second
Auto / Manual
Auto / WDR (120dB)
20x
360° endless, 0° ~ 60°/sec;
+90° ~ 90°, 0° ~ 40°/sec
128
Pan: 100°/s, Tilt, 80°/s
Up to 128 Presets, IR Range of 100 Mtr.
Auto(ICR) / Color / B/W
H.265 / H.264
Main Stream: 25/30fps@1080P / 720P, Sub Stream: 25/30fps@D1/CIF
G.722.1, G.711-a law, G.711-u law, MP2L2, G.726, AAC, PCM
TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, FTP, 802.1x, QoS, HTTPS, IPv6 (SIP, SRTP, optional), ONVIF, PSIA, CGI, ISAPI
20 users
Supports
-35°C ~ +55°C
IP66
13kg
DC-12V (50VA)



Accessories:

Special Anti vibration Bracket for Vehicle PTZ camera

