

CP- SMR-H0401-S10-PG

4 Ch. AHD + 1 Ch. 720p H.264 Mobile DVR



Main Features

- Supports 4 channels AHD +1 channels 720P
- Supports Hard disk for main recording
- Built-in 3G/4G for live view and remote management
- Supports GPS for location tracking
- Vibration-resistant design to meet various environment needs.
- Supports USB2.0 high speed backup
- Pre-recording max. 60 mins
- Tamper-proof watermarks
- Modular design for easy maintenance



CP-SMR-H0401-S10-PG

4 Ch. AHD + 1 Ch. 720p H.264 Mobile DVR

Feature

Operating System
Control Mode
Operation Interface
Video Systems
Total Resource
Video Input
Video Output
Recording Mode
Audio Input
Audio Output
Pre-recording
Image Resolution
Post-recording
Display Split
OSD
Image Quality
GPS
Search Mode
Sensors
USB
Hard Disk
MIC
Video/Audio Compression
Ethernet
3G Support
Serial Ports
Power Input
Power Output
Power Consumption

Specification

Linux 3.0.8
Easy Check
Semi-transparent GUI
Electrical level: 1Vpp Impedance : 75Ω NTSC/PAL Optional
PAL: (4x25)fps WD1+30fps 720P(IPC) Or (4x12)fps 720P(AHD)+30fps 720P(IPC) NTSC: (4x30)fps WD1 +30fps 720P (4x15)fps 720P(AHD)+30fps 720P(IPC)
4 channels WD1+1 channel 720P
1 channels
Boot up/Manual/Schedule/Alarm
5channels (1 channel IPC audio input)
1 channels
0~60 munites
Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P
0-30 minutes
1/4/9
GPS information, alarm, vehicle No., speed, date/time
1-8 levels adjustable (1 is the best)
Location tracking, speed detection and time sync
Date/time, channel, event
8 Inputs, 2 Outputs
USB 2.0 × 1
2.5" SATA HDD
1 MIC interface
H.264/ADPCM
6-pin DJ(100M x 1, PON power supply)
3G/4G
RS232 × 1
DC8-36V
5V@1A
32W

CP- SMR-H0401-S10-PG

4 Ch. AHD + 1 Ch. 720p H.264 Mobile DVR

Feature

Dimension (W×H×D)

Weight

Operating Temperature

Relatively Operating Humidity

Certification

Specification

206mm × 190mm × 70.4mm

1.24Kg.

-40°C- +70°C(With heater) or -10°C- +70°C

8%~90%(no Condense)

CE, FCC