

# CP- SMR-H0402-S11-P

4 Ch. WD1 + 2 Ch. 720P H.264 Mobile DVR



## Main Features

- Supports 4 channels WD1 + 2 channels 720P
- Supports Hard Disk for main recording
- Supports GPS for location tracking
- Supports SD card for mirror recording
- Supports USB2.0
- Pre-recording max. 60 mins
- Supports data recovery technology
- Supports 360 degree anti-vibration
- Modular design for easy maintenance



# CP-SMR-H0402-S11-P

## 4 Ch. WD1 + 2 Ch. 720P H.264 Mobile DVR

### Feature

Operating System  
Operation Interface  
Control Mode  
Video Systems  
Total Resource  
Video Input  
Video Output  
Recording Mode  
Audio Input  
Pre-recording  
Audio Output  
Post-recording  
Image Resolution  
Display Split  
Playback  
Mirror Recording  
OSD  
Image Quality  
GPS  
Search Mode  
Sensors  
USB  
Ethernet  
Video/Audio Compression  
Storage  
Serial Ports  
Power Input  
Power Output  
Dimension (WxHxD)  
Weight

### Specification

Linux 3.0.8  
Semi-transparent GUI  
Easy Check, network, mouse  
Electrical level: 1Vpp Impedance : 75Ω NTSC/PAL Optional  
(4 x 25)FPS WD1 @ PAL / (4 x 30)FPS WD1 @ NTSC +(2 x 30)FPS 720P  
4 channels WD1+2 channels 720P  
1 channels  
Boot up/Manual/Schedule/Alarm (sensor trigger, speed, acceleration, video loss, tempera-  
6 channels (Including IPC x 2)  
0~60 minutes  
1 channels  
0-30 minutes  
Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digi-  
tal: 720P  
1/4/9  
1 channel by local playback  
Supports  
GPS information, alarm, vehicle No., speed, date/time  
1-8 levels adjustable (1 is the best)  
Location tracking, speed detection and time sync  
Date/time, channel, event  
8 Inputs, 2 Outputs  
USB 2.0 x 2  
RJ45 port (10/100M)  
H.264/ADPCM  
2.5" SATA hard disk x 1 (Up to 2 TB)  
RS232 x 2 / RS485 x 2  
DC8-36V  
12V@1A, 5V@1A  
255.3mm x 150mm x 89.1mm  
2.2Kg.

# CP- SMR-H0402-S11-P

4 Ch. WD1 + 2 Ch. 720P H.264 Mobile DVR

## Feature

Operating Temperature

Relatively Operating Humidity

Certification

## Specification

-40°C- +70°C(With heater) or -10°C- +70°C

8%~90%(no Condense)

CE, FCC