

CP- SMR-H0402-S11-PG**4 Ch. WD1 + 2 Ch. 720P H.264 Mobile DVR****Main Features**

- Supports 4 channels WD1 + 2 channels 720P
- Supports Hard Disk for main recording
- Supports GPS for location tracking
- Supports SD card for mirror recording
- Built-in 3G/4G for live view and remote management
- Supports USB2.0
- Pre-recording max. 60 mins
- Supports data recovery technology



**Product casing and specifications are subject to change without prior notice*

CP-SMR-H0402-S11-PG

4 Ch. WD1 + 2 Ch. 720P H.264 Mobile DVR

Feature

Operating System

Control Mode

Operation Interface

Video Systems

Total Resource

Video Input

Video Output

Recording Mode

Audio Input

Pre-recording

Audio Output

Post-recording

Image Resolution

Display Split

Mirror Recording

Image Quality

Playback

OSD

GPS

Sensors

Search Mode

USB

Ethernet

Video/Audio Compression

3G Support

Storage

Serial Ports

Power Input

Power Output

Specification

Linux 3.0.8

Easy Check, IR Remote Control, Network, Mouse

Semi-transparent GUI

Electrical level: 1Vpp Impedance : 75Ω NTSC/PAL Optional

(4 x 25)FPS WD1 @ PAL / (4 x 30)FPS WD1 @ NTSC +(2 x 30)FPS 720P

4 channels WD1+2 channels 720P

1 channels

Boot up/Manual/Schedule/Alarm (sensor trigger, speed, acceleration, video loss, temperature)

6 channels (Including IPC x 2)

0~60 minutes

1 channels

0-30 minutes

Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P

1/4/9

Supports

1-8 levels adjustable (1 is the best)

1 channel by local playback

GPS information, alarm, vehicle No., speed, date/time

Location tracking, speed detection and time sync

8 Inputs, 2 Outputs

Date/time, channel, event

USB 2.0 x 2

RJ45 port (10/100M)

H.264/ADPCM

Supports 3G/4G, EVDO/WCDMA/TDD-LTE/FDD-LTE

2.5" SATA hard disk x 1(Up to 2 TB)

RS232 x 2 / RS485 x 2

DC8-36V

12V@1A, 5V@1A

CP- SMR-H0402-S11-PG

4 Ch. WD1 + 2 Ch. 720P H.264 Mobile DVR

Feature

Dimension (W×H×D)

Weight

Operating Temperature

Relatively Operating Humidity

Certification

Specification

255.3mm x 150mm x 89.1mm

2.2Kg.

-40°C- +70°C(With heater) or -10°C- +70°C

8%~90%(no Condence)

CE, FCC