

CP- SMR-H0804-S11

8 Ch. WD1 + 4 Ch. 720P H.264 Mobile DVR



Main Features

- Modular design for easy maintenance
- Supports 8 channels WD1+ 4 channels IPC (720P) or 4 channels WD1 8 channels IPC (720P)
- Built-in 3G for live view and remote monitoring
- H.264 video compression
- Supports 2.5" 2TB hard disk storage and SD card for mirror recording
- Built-in GPS
- Built-in G-sensor, Built-in heater (optional)
- Internal WIFI 802.11N supported for all the regular video files and alarm files download
- Revolutionary anti-vibration technology for 360 degree installation

CP-SMR-H0804-S11

8 Ch. WD1 + 4 Ch. 720P H.264 Mobile DVR

Feature	Specification
Operating System	Linux 3.0.8
Operation Interface	Semi-transparent GUI
Control Mode	Preview, Recording, Playback, Network, Locating, Mouse
Video Systems	Electrical level: 1Vpp Impedance : 75Ω NTSC/PAL Optional
Total Resource	(8 x 25)FPS WD1 @ PAL / (8 x 30)FPS WD1 @ NTSC +(4 x 30)FPS 720P or (4 x 25)FPS WD1 @ PAL / (4 x 30)FPS WD1 @ NTSC +(4 x 30)FPS 720P
Video Input	8channel WD1+4channel IPC(720P)/4channel WD1+8channel IPC (720P)
Video Output	2 channels
Recording Mode	Manual/schedule/Alarm (sensor trigger, speed, acceleration, video loss, temperature)
Audio Input	8channels(12 channels if connects with IPCX4)
Pre-recording	0~60 minutes
Audio Output	2 channels
Display Split	1/4/9
Image Resolution	Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P
Post-recording	0-30 minutes
GPS	Location tracking, speed detection and time sync
Image Quality	8 Levels adjustable
Mirror Recording	Support
Search Mode	Date/time, channel, event
Sensors	8 Inputs, 2 Outputs
USB	USB 2.0 x 2
Hard Disk	2.5" SATA HDD
Ethernet	RJ45 port (10/100M)
Video/Audio Compression	H.264/ADPCM
WiFi	802.11b/g/n (optional)
3G Support	3G/4G EVDO/WCDMA/TDD-LTE/FDD-LTE
Serial Ports	RS232 x 2, RS485 x 2
Power Input	DC8-36V
Power Output	1A@12V, 1A@5V
Dimension (WxHxD)	292.5mm x 215mm x 91.6mm (including shelf and back cover)
Weight	2.6kg
Operating Temperature	-40°C- +70°C(With heater) or -10°C- +70°C

CP- SMR-H0804-S11

8 Ch. WD1 + 4 Ch. 720P H.264 Mobile DVR

Feature

Relatively Operating Humidity
Certification

Specification

8%~90%
CE, FCC