

CP- SMR-H0804-S11-P

8 Ch. WD1 + 4 Ch. 720P(IPC) / (WD1) H.264 Mobile DVR



Main Features

- Supports 8 channels WD1+ 4 channels IPC (720P)
or 4 channels WD1 + 8 channels IPC (720P)
- Supports Hard Disk for main recording
- Supports 360 degree anti-vibration
- Supports GPS for location tracking
- Supports SD card for mirror recording
- Supports USB2.0
- Supports Built-in heater (optional)
- Pre-recording max. 60 mins
- Built-in G-sensor



*Product casing and specifications are subject to change without prior notice

CP- SMR-H0804-S11-P

8 Ch. WD1 + 4 Ch. 720P(IPC) / (WD1) H.264 Mobile DVR

Feature

Operating System

Control Mode

Operation Interface

Video Systems

Total Resource

Video Input

Video Output

Recording Mode

Audio Input

Audio Output

Pre-recording

Post-recording

Display Split

Image Resolution

Mirror Recording

Image Quality

Playback

GPS

OSD

Sensors

Search Mode

USB

Ethernet

Video/Audio Compression

Storage

Serial Ports

Power Input

Power Output

Dimension (WxHxD)

Specification

Linux 3.0.8

Easy Check, IR Remote Control, Network

Semi-transparent GUI

Electrical level: 1Vpp Impedance: 75Ω NTSC/PAL Optional

(8 x 25)FPS WD1 @ PAL / (8 x 30)FPS WD1 @ NTSC +(4 x 30)FPS 720P or (4 x 25)FPS WD1 @ PAL / (4 x 30)FPS WD1 @ NTSC +(4 x 30)FPS 720P

8 Channel WD1+4 Channel IPC(720P)/4 Channel WD1+8 Channel IPC (720P)

2 channels

Manual/schedule/Alarm (sensor trigger, speed, acceleration, video loss, temperature)

8 Channels(12 channels if connects with IPCX4)

2 Channels

0~60 munites

0-30 minutes

1/4/9

Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC, WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P

Supports

8 Levels adjustable

1/4 channels by local playback

Location tracking, speed detection and time sync

GPS/BD information, alarm, temperature, acceleration, voltage, device information, software version, MCU version, network status

8 Inputs, 2 Outputs

Date/time, channel, event

USB 2.0 x 2

RJ45(1000M)

H.264/ADPCM

Supports 2.5" hard disk up to 2TB, SD Card x 1

RS232 x 2 / RS485 x 2

DC8-36V

1A@12V,1A@5V

292.5mm x 215mm x 91.6mm

CP- SMR-H0804-S11-P

8 Ch. WD1 + 4 Ch. 720P(IPC) / (WD1) H.264 Mobile DVR

Feature

Weight

Operating Temperature

Relatively Operating Humidity

Certification

Specification

2.6 kg

-40 \times +70 \times (With heater) or -10 \times +70 \times

8%~90%

CE, FCC