

CP- SMR-H1608-S21-PG

16 Ch. WD1 + 8 Ch. 720P(IPC) H.264 Mobile DVR



Main Features

- Supports 16 Channels WD1 + 8 Channels IPC (720P)
- Supports 360 degree anti-vibration
- Supports GPS for location tracking
- Supports SD card for mirror recording
- Supports Hard Disk for main recording
- Supports USB2.0
- Pre-recording max. 60 mins
- Built-in 3G/4G for live view and remote management



CP-SMR-H1608-S21-PG

16 Ch. WD1 + 8 Ch. 720P(IPC) H.264 Mobile DVR

Feature

Operating System

Control Mode

Operation Interface

Video Systems

Total Resource

Video Input

Video Output

Recording Mode

Audio Input

Audio Output

Pre-recording

Display Split

Image Resolution

Post-recording

Playback

Image Quality

GPS

OSD

Mirror Recording

Search Mode

Sensors

USB

Ethernet

Video/Audio Compression

3G Support

Storage

Serial Ports

Power Input

Power Output

Power Consumption

Specification

Linux 3.0.8

Easy Check, IR Remote Control, Network, Mouse

Graphical User Interface

Electrical level:1Vpp Impedance:75Ω NTSC/PAL Optional

(16 x 25)FPS WD1 @ PAL/(16 x 30)FPS WD1@NTSC +(8 x 30)FPS 720P

16 channels WD1+8channels IPC (720P)

3 channels

Boots up/manual/schedule/Alarm event recording(sensor trigger, speed, external acceleration sensor, alarm button)

24 channels(8 channels IPC)

3 channels

0~60 minutes

1/4/9

Analog: PAL: WD1, WHD1, WCIF, D1, HD1, CIF, NTSC: WD1, WHD1, WCIF, D1, HD1, CIF; Digital: 720P

0-30 minutes

1/4 channels by local playback

8 levels adjustable

Location tracking, speed detection and time sync

Locating, alarm, vehicle number, speed and date/time

Supports

Date/time, channel, event

8 Inputs, 2 Outputs

USB 2.0 x 2 (1 at front panel, 1 at rear panel)

RJ45(1000M) x 2

H.264/ADPCM

Supports 3G/4G, EVDO/WCDMA/TDD-LTE/FDD-LTE

Supports 2.5" SATA hard disk x 2, SD Card x 1

RS232 x 2 / RS485 x 2

DC8-36V

12V@1A, 5V@1A

Impulse current: input 13.5V@10A Working current: input 13.5V@5A input 27V@2.5A





CP- SMR-H1608-S21-PG

16 Ch. WD1 + 8 Ch. 720P(IPC) H.264 Mobile DVR

Feature

Dimension (W×H×D)

Weight

Operating Temperature

Relatively Operating Humidity

Certification

Specification

324.6mm x 238mm x 116mm

4.2 Kg

-10°C ~ +70°C or -40°C ~ +70°C(heated)

8%~90%

CE, FCC



**Product casing and specifications are subject to change without prior notice*

www.activesystemintegration.com

9994126666