

CP- UNR-404T2-MW2

4 Channel PoE Mobile Standalone DVR



Main Features

- Up to 4 channel 1080P cameras Realtime live view
- H.264/ H.265/MJPEG dual codec decoding
- Max 200 Mbps recording rate
- Built-in module (GPS/3G/ Dual 4G/ Wi-Fi optional)
- 4 PoE Ports
- Support 2 SATA HDDs, 1 SD Card, 3 USB Port
- Aviation connectors adopted
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UNR-404T2-MW2

4 Channel PoE Mobile Standalone DVR



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
Video Input
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
SD Card
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Max User Account
Record Interval
Wi-Fi
GPS
Ethernet

Specification

Dual-core embedded processor
4 channel
Embedded Linux
1ch Mic in, 1ch Mic out
4Ch.
1 HDMI, 1 VGA, 2 TV
H.264/H.265/G.711/PCM
1920×1080, 1280×1024, 1280×720, 1024×768
Max 200 Mbps
1/4
4 rectangular zones (each camera)
Zones: 396(22×18)
Supports
Supports
8 channel
3 channel
iPhone, iPad, Android, Windows Phone
2 SATA ports
1 SD card
Recording, PTZ, Tour, Alarm out, Email, FTP, Snapshot, Buzzer & Screen tips
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device/eSATA Device/Network/ External HDD
3 USB Port, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, G-sensor
128 users
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Built-in 3G / Dual 4G / Wi-Fi module (optional)
Built-in high accurate GPS module (optional)
1RJ-45 port (10/100/1000M)



CP- UNR-404T2-MW2

4 Channel PoE Mobile Standalone DVR



Feature

Protocols
Power Supply
Power Consumption
Working Temp
Anti Vibration
Casing
Regulatory
Dimensions
Weight

Specification

TCP/IP, UDP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Email, Alarm Server
6V~36V
≤15W
-30°C (heater optional)~+60°C / 10%~95%RH / 86~106kpa
As Per EN50155 standard for various Mobile Vehicle and Railway applications
Aluminium Alloy
CE, FCC, RoHS and EN50155
180mm × 208mm × 100mm
3 KG (Without HDD)