

# CP- UNR-408T2-MF

## 8 Channel PoE Mobile Standalone DVR



### Main Features

- Up to 8 channel 1080P Cameras Realtime live view
- H.264 / MJPEG dual codec decoding
- Max 200 Mbps recording rate
- Built-in 3G/4G/Wi-Fi module (optional)
- 8 PoE Ports, Support 2 SATA HDDs, 2 USB2.0
- Support 2 SATA HDDs, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



\*Product casing and specifications are subject to change without prior notice

# CP- UNR-408T2-MF

## 8 Channel PoE Mobile Standalone DVR



### Feature

Processor  
Operating System  
Two-way Talk  
Video Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Privacy Masking  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Camera Blank  
Alarm Input  
Alarm Output  
Smart Phone  
Hard Disk  
SD Card  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Record Interval  
Max User Account  
Interface Ports  
Wi-Fi

### Specification

Dual-core embedded processor  
Embedded Linux  
1ch Mic in, 1ch Mic out (aviation connector)  
8 channel  
1 HDMI, 1VGA, 2TV  
PAL: 625 Lines, 50f/s; NTSC: 525 Lines, 60f/s  
H.264 / G711A  
1920×1080, 1280×1024, 1280×720, 1024×768  
Max 200 Mbps  
1/4/8/9  
4 rectangular zones (each camera)  
8 Ch.  
1 Ch.  
Zones: 396(22×18)  
Supports  
Supports  
8 channel  
2 channel  
iPhone, iPad, Android, Windows Phone  
2 SATA ports up to 4TB, 1 eSATA port  
1 SD card  
Recording, PTZ, Tour, Alarm out, Email, FTP, Snapshot, Buzzer & Screen tips  
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop  
Time/Date, Alarm, Motion Detection & Exact search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device / eSATA Device / Network / Internal HDD  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
128 users  
3 USB 2.0, 1 RS232, 1 RJ45, 1 RS485, 1 eSATA, Supports G-Sensor, UPS, CAN Port  
Built-in 3G / Wi-Fi module (optional)



# CP- UNR-408T2-MF

## 8 Channel PoE Mobile Standalone DVR



### Feature

GPS  
Ethernet  
Protocols  
Power Supply  
Power Consumption  
Working Temp  
Dimensions  
Weight

### Specification

GPS / BDS (optional)  
RJ-45 port (10/100M)  
HTTP, IPv4, TCP/IP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Filter  
6V~36V  
≤15W  
-10°C ~+60°C / 10%~95%RH / 86~106kpa  
180mm × 208mm × 100mm  
3 KG (Without HDD)