

**CP- UNC-TB13FL6-M****1.3 MP HD IR Bullet Camera - 60Mtr.****Main Features**

- 1/3" 1.3MP PS CMOS Image Sensor
- 25/30fps@1.3M(1280x960)
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.7 -12mm Varifocal Lens
- IR Range of 60 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



\*Product casing and specifications are subject to change without prior notice

# CP- UNC-TB13FL6-M

## 1.3 MP HD IR Bullet Camera - 60Mtr.



### Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Lens  
Gain Control(AGC)  
Back Light Compensation  
S/N Ratio  
Video Compression  
Video Streaming  
Resolution  
Privacy Mask  
ICR

### Specification

1/3" 1.3MP Progressive scan CMOS  
0.01Lux/F1.4(Color), 0Lux/F1.4(IR on)  
Auto/Manual, 1/3(4)~1/10000s  
Auto/Manual  
2.7 -12mm Varifocal Lens  
Auto/Manual  
BLC/ HLC/ DWDR  
More than 50dB  
H.264/MJPEG  
Main Stream: 1.3M (1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)  
1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240)  
Up to 4 areas  
Auto(ICR)/Color/B/W

Protocol  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

Ethernet  
RJ-45 (10/100Base-T)

User Account  
20 Users

Smart Phone  
iPhone, iPad, Android, Windows Phone

IR  
IR Range of 60 Mtr.

Micro SD  
Micro SD, Max 128GB

Operating Temperature  
-30°C~+60°C , Less than 95%RH

Power Source  
DC12V, PoE (802.3af)

Power Consumption  
<6W

Weatherproof Standard  
IP67

Dimension  
72mm × 80mm × 212.8mm

Weight  
650g