


# CP-UNC-TD13L4

1.3 MP HD IR Bullet Camera - 40Mtr.



## Main Features

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- Max 25/30fps@1.3MP
- H.264 and MJPEG triple-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Smart Detection supported
- 3.6mm fixed lens (6mm optional)
- IR Range of 40 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TD13L4

## 1.3 MP HD IR Bullet Camera - 40Mtr.

### Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Gain Control(AGC)  
Lens  
S/N Ratio  
Back Light Compensation  
Video Streaming  
Resolution  
Privacy Mask  
ICR  
Protocol  
Smart Detection  
Ethernet  
User Account  
Smart Phone  
IR  
Operating Temperature  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

### Specification

1/3" 1.3Megapixel progressive scan CMOS  
0.01Lux/F2.0(Color), 0Lux/F2.0(IR on)  
Auto/Manual, 1/3(4)~1/10000s  
Auto/Manual  
Auto/Manual  
3.6mm(6mm optional)  
More than 50dB  
BLC / HLC / DWDR  
Main Stream: 1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1~14/7fps)  
1.3M(1280x960)/720P(1280x 720)/ D1(704x 576/704x 480) /CIF(352x 288/352x 240)  
Up to 4 areas  
Auto(ICR)/Color/B/W  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI  
Tripwire, Intrusion, Scene Change, Face detect  
RJ-45 (10/100Base-T)  
20 Users  
iPhone, iPad, Android, Windows Phone  
IR Range of 30 Mtr.  
-40°C~+60°C, Less than 95% RH  
DC12V, PoE (802.3af)  
Max 5.5W  
IP67  
70mm x 70mm x 180mm  
0.4kg(0.528kg with packaging)