

# CP- UNC-TE13FL3-M

1.3 MP HD IP IR Bullet Camera - 30Mtr.



## Main Features

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 30 Mtrs.
- 2.8~12mm varifocal lens
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TE13FL3-M

## 1.3 MP HD IP IR Bullet Camera - 30Mtr.

### Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Lens  
Gain Control(AGC)  
S/N Ratio  
Back Light Compensation  
Video Compression  
Video Streaming  
Resolution  
Privacy Mask  
ICR  
Audio Input  
Audio Output  
Audio Compression  
Alarm IN  
Alarm Out  
Interface  
Protocol  
Ethernet  
User Account  
IR  
Smart Phone  
Micro SD  
Operating Temperature  
Power Source  
Power Consumption  
Weatherproof Standard  
Regulatory

### Specification

1/3" 1.3Megapixel CMOS  
0.01Lux/F1.2 (Color), 0.005Lux/F1.2(B/W);0Lux/F1.2(IR on)  
Auto/Manual, 1/3(4)~1/10000s  
Auto  
2.8mm~12mm  
Auto/Manual  
More than 50 dB  
BLC / HLC / DWDR  
H.264/MJPEG  
Main Stream:1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)  
1.3M(1280×960) /720P(1280×720) /D1(704×576) / CIF(352×288)  
Up to 4 areas  
Auto(ICR)/Color/B/W  
1 Ch.  
1 Ch.  
G.711a / G.711u / PCM  
2 Ch.  
1 Ch.  
1 RS485, 1 RJ45  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S  
RJ-45 (10/100Base-T)  
10 users  
IR Range of 30 Mtr.  
iPhone, iPad, Android, Windows Phone  
Micro SD, Max 64GB  
-20°C~+60°C(-H: -40°C~+60°C), Less than 95% RH  
DC12V (AC24V optional) , PoE (802.3af)  
Max 7.5W(AC 24V:Max 11W)  
IP66  
CE, FCC and RoHS

# CP- UNC-TE13FL3-M

1.3 MP HD IP IR Bullet Camera - 30Mtr.

## Feature

Dimension

Weight

## Specification

φ104×306.7mm

1.25kg