

# CP- UNC-TE13ZL5-MD

1.3 MP HD IP IR Bullet Camera - 50 Mtr.



## Main Features

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)
- WDR(120dB), Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 2.7mm ~12mm motorized lens
- Supports PoE, Micro SD Card, IP67
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TE13ZL5-MD

## 1.3 MP HD IP IR Bullet Camera - 50 Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control(AGC)  
 Back Light Compensation  
 Video Compression  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Video Output  
 Privacy Mask  
 ICR  
 Audio Input  
 Audio Output  
 Audio Compression  
 Alarm IN  
 Alarm Out

### Specification

1/3" 1.3Megapixel CMOS  
 0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)  
 Auto/Manual, 1/3(4)~1/10000s  
 Auto/Manual  
 2.7mm~12mm Motorized Lens  
 Auto/Manual  
 BLC / HLC / WDR(120dB)  
 H.264/MJPEG  
 More than 50 dB  
 Main Stream:1.3M/720P(1 ~ 25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P (1~25/30fps)  
 1.3M(1280×960)/720P(1280×720)/D1(704×576/704×480)/CIF(352  
 1 Port  
 Up to 4 areas  
 Auto(ICR)/Color/B/W  
 1 Ch.  
 1 Ch.  
 G.711a / G.711u/AAC  
 2 Ch.  
 1 Ch.

### Protocol

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S

### Smart Detection

Tripwire, Intrusion, Abandoned/Missing, Scene Change, Audio detect, Face detect

### Ethernet

RJ-45 (10/100Base-T)

### User Account

20 users

### IR

IR Range of 50 Mtr.

### Smart Phone

iPhone, iPad, Android, Windows Phone

### Micro SD

Micro SD, Max 128GB

### Operating Temperature

-30°C~+60°C, Less than 95% RH

### Power Source

DC12V, PoE(802.3af)

### Power Consumption

<11.5W (with IR on, motorized lens working)

# CP- UNC-TE13ZL5-MD

1.3 MP HD IP IR Bullet Camera - 50 Mtr.

## Feature

Weatherproof Standard

Regulatory

Dimension

Weight

## Specification

IP67

CE, FCC and RoHS

272.9 mm × 94.9mm × 94.9mm

1.1kg