

CP-UNC-TH4K12ZL5-VM

12MP 4K IP IR Bullet Camera - 50Mtr.



Main Features

- 1/1.7" 12Megapixel progressive scan CMOS
- Max 15fps@12 MP / 25/30fps@4K
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 4.1mm ~16.4mm motorized lens
- IR Range of 50 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-TH4K12ZL5-VM

12MP 4K IP IR Bullet Camera - 50Mtr.



Feature

Image Sensor
 Effective Pixels
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control(AGC)
 Lens
 S/N Ratio
 Back Light Compensation
 Video Compression
 Video Output
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Bit Rate
 Protocol
 Smart Detection
 Ethernet
 User Account
 IR
 Smart Phone

Specification

1/1.7" 12MP Progressive scan CMOS
 4000(H) x 3000(V)
 0.05Lux/F1.4(Color); 0Lux/F1.4(IR on)
 Auto/Manual, 1/3(4)~1/100000s
 Auto/Sunny/Night/Outdoor/Customized
 Auto/Manual
 4.1mm~16.4mm
 More than 50dB
 BLC / HLC / DWDR
 H.264/H.264B/H.264H/ MJPEG
 1 channel BNC (1.0Vp-p,75Ω)
 12M(4000x3000)/8M(4096x 2160)/8M(3840x 2160)/1080P(1920x 1 080)/720P(1280x 720) /
 D1(704x 576) /CIF(352x 288)
 Main Stream: 12M(1~15fps)/ 8M(4096x2160) (1~25/30fps), Sub Stream: D1/CIF(1 ~
 25/30fps), Third Stream: 1080P/720P/D1(1 ~ 25/30fps)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 Up to 4 areas
 1 Channel
 1 Channel
 G.711a / G.711u/AAC
 2 Channel
 1 Channel
 H.264: 32Kbps~ 16Mbps
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP,
 DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour,802.1x, ONVIF, PSIA, CGI
 Tripwire, Intrusion,Scene change, Missing/Abandoned, Audio detect, Defocus detect, Face
 RJ-45 (10/100/1000Base-T)
 20 Users
 IR Range of 50 Mtr.
 iPhone, iPad, Android Phone



*Product casing and specifications are subject to change without prior notice

CP- UNC-TH4K12ZL5-VM

12MP 4K IP IR Bullet Camera - 50Mtr.



Feature

Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

Micro SD, Max 128GB
-30°C~+60°C, Less than 95% RH
DC12V(AC24V optional), PoE (802.3at)
Max24W (IR on)
IP67
272.9mm× 94.3mm× 94.3mm
0.8Kg