

CP- ENC-T21L3-VMDS

2 MP Full HD WDR IR Network Bullet Camera - 30Mtr.



Main Features

- 1/2.7" 2MP CMOS Image Sensor
- Max 25fps@2MP
- H.265/ H.264 Video Compression
- WDR(100dB), Day/Night (ICR), AWB, AGC, BLC
- 3.6mm lens (6mm optional)
- IR Range of 30 Mtrs, IP66, SD Card
- Mobile Software: RMOB
- CMS Software: RVMS



*Product casing and specifications are subject to change without prior notice

CP- ENC-T21L3-VMDS

2 MP Full HD WDR IR Network Bullet Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
White Balance
Gain Control (AGC)
Lens
Video Compression
Back Light Compensation
Video Streaming
Resolution
Frame Rate
ICR
Audio Input
Audio Output
Alarm IN
Alarm Out
WDR
Protocol
Ethernet
Smart Phone
IR
Micro SD
Operating Temperature
Power Source
Weatherproof Standard
Dimension
Weight

Specification

1/2.7" 2MP CMOS Image Sensor
0.01Lux@F1.2(Color)/0.001Lux@F1.2(B/W)
Auto/Manual
Auto/Manual
3.6mm Lens (6mm optional)
H.265 / H.264
Auto/Manual
Dual Stream
1080P(1920x1080) / 720P(1280x720) / D1(704x576) / CIF(352x288)
Main Stream : 1080P@25fps , Sub-Stream: D1
IR CUT
1 channel
1 channel
2 Channel
1 channel
WDR (100dB)
ONVIF Support (profile S)
RJ-45 (10/100Base-T)
iPhone, iPad, Android
IR Range of 30 Mtr.
SD Card, Max 32G
-20°C~+65°C
DC12V±10%, PoE
IP66
210mm x 62.5mm x 59mm
355g