

# CP- ENC-T21L5-VMDS

2 MP Full HD WDR IR Network Bullet Camera - 50 Mtr.



## Main Features

- 1/2.7" 2MP CMOS Image Sensor
- Max 25fps@2MP
- H.265/ H.264 Video Compression
- WDR(100dB), Day/Night (ICR), AWB, AGC, BLC
- 3.6mm lens (6mm optional)
- IR Range of 50 Mtrs, IP66, SD Card
- Mobile Software: RMOB
- CMS Software: RVMS



\*Product casing and specifications are subject to change without prior notice

# CP- ENC-T21L5-VMDS

2 MP Full HD WDR IR Network Bullet Camera - 50 Mtr.



## Feature

Image Sensor  
Minimum Illumination  
White Balance  
Gain Control (AGC)  
Lens  
Video Compression  
Back Light Compensation  
Video Streaming  
Resolution  
Frame Rate  
ICR  
Audio Input  
Audio Output  
Alarm IN  
Alarm Out  
WDR  
Protocol  
Ethernet  
Smart Phone  
IR  
Micro SD  
Operating Temperature  
Power Source  
Weatherproof Standard  
Dimension  
Weight

## Specification

1/2.7" 2MP CMOS Image Sensor  
0.01Lux@F1.2(Color)/0.001Lux@F1.2(B/W)  
Auto/Manual  
Auto/Manual  
3.6mm Lens (6mm optional)  
H.265 / H.264  
Auto/Manual  
Dual Stream  
1080P(1920x1080) / 720P(1280x720) / D1(704x576) / CIF(352x288)  
Main Stream : 1080P@25fps , Sub-Stream: D1  
IR CUT  
1 channel  
1 channel  
2 Channel  
1 channel  
WDR (100dB)  
ONVIF Support (profile S)  
RJ-45 (10/100Base-T)  
iPhone, iPad, Android  
IR Range of 50 Mtr.  
SD Card, Max 32G  
-20°C~+65°C  
DC12V±10%, PoE  
IP66  
161.2mm x 97.45mm x 87.3mm  
891g