


CP-UNC-BH21-VMD-V2

2 MP Network WDR Box Camera



Main Features

- 1/1.9" 2MP PS CMOS Image Sensor
- 50/60fps@1080P(1920x1080)
- H.265 and H.264 triple-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, AWB, AGC, BLC
- C/CS Mount Lens, PoE, SD Card
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-BH21-VMD-V2

2 MP Network WDR Box Camera



Feature

Image Sensor
 Effective Pixels
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Iris Control
 Auto Exposure
 Gain Control (AGC)
 Video Compression
 S/N Ratio
 Back Light Compensation
 Video Streaming
 Resolution
 Video Output
 Special Feature
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Pre/Post Alarm Buffer
 Watermark
 Bit Rate
 Interface
 Protocol
 Smart Detection

Specification

1/1.9" 2MP progressive scan CMOS
 1920(H) x 1080(V)
 0.001Lux/F1.2 (Color), 0.0001Lux/F1.2 (B/W)
 Auto/Manual, 1/1~1/100000s
 Auto/Natural/Street Lamp/Outdoor/Manual
 C/CS Mount Lens
 Auto
 Auto/ Manual
 Auto/Manual
 H.265/H.264
 More than 50dB
 BLC / HLC / WDR(120dB)/ SSA
 Main Stream: 1080P(1~50/60fps) , Sub Stream: D1 (1 ~ 50/60fps) , Third Stream: 1080P (1~50/60fps)
 1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480)/ VGA (640x480)/ CIF(352x288/342x240)
 1 port
 Privacy Mask, Motion Detection, Active Tampering Alarm
 Auto (ICR)/Color/B/W
 Off / On (4 Zone)
 2 Channel , 1 Built-in Mic
 1 Channel
 G.711a/ G.711Mu/ AAC/ G.726
 2 Channel In
 2 Channel Out
 Supports
 Supports
 H.264: 24~ 10240Kbps , H.265: 14~ 6144Kbps
 1 RS485
 HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; SSL, IGMP, DDNS; PPPOE; IPv4/ v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP, ONVIF (Profile S), PSIA, CGI
 Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, People Counting, Heat Map



*Product casing and specifications are subject to change without prior notice

CP- UNC-BH21-VMD-V2

2 MP Network WDR Box Camera



Feature

Ethernet
User Account
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Dimension
Weight

Specification

RJ-45 (100/1000Base-T)
20 Users
iPhone, iPad, Android Phone
Max 128GB
-30°C~+60°C , Less than 95%RH
DC12V, AC24V, PoE(802.3af)
<6.5W
161.6mm x 85.5mm x 74.0mm
0.72Kg