

CP- UNC-BH21-VMD-V3**2 MP Network WDR Box Camera****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- 50/60fps@1080P(1920×1080)
- H.265 and H.264 triple-stream encoding
- WDR(140dB), Day/Night (ICR), 3D-DNR, AWB, AGC, BLC
- C/CS Mount Lens, PoE, SD Card
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-BH21-VMD-V3

2 MP Network WDR Box Camera



Feature

Image Sensor
Effective Pixels
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
S/N Ratio
Video Compression
Back Light Compensation
Video Streaming
Resolution
Video Output
Motion detection
Privacy Mask
ICR
ROI
Audio Input
Audio Compression
Audio Output
Alarm IN
Alarm Out
Pre/Post Alarm Buffer
Watermark
Bit Rate
Interface
Protocol

Specification

1/2.8" 2MP progressive scan CMOS
1920(H) x 1080(V)
0.003Lux/F1.2(Color,1/3s,30IRE) 0.03Lux/F1.2(Color,1/30s,30IRE) 0.001Lux/F1.2(B/W,1/3s,30IRE) 0.01Lux/F1.2(B/W,1/30s,30IRE)
Auto/Manual, 1/1~1/100000s
Auto/Natural/Street Lamp/Outdoor/Manual
C/CS Mount Lens
Auto/Manual
More than 50dB
H.265+/H.265/H.264+/H.264
BLC / HLC / WDR(140dB)/ SSA
Main Stream: 1080P(1~50/60fps) , Sub Stream: D1 (1 ~ 50/60fps) , Third Stream: 1080P (1~50/60fps)
1080P(1920x1080)/ 1.3M(1280x960)/ 720P(1280x720)/ D1(704x576/704x480)/ VGA (640x480)/ CIF(352x288/342x240)
1 port
Off / On (4 Zone, Rectangle)
Off / On (4 Area, Rectangle)
Auto (ICR)/Color/B/W
Off / On (4 Zone)
2 Channel , 1 Built-in Mic
G.711a/ G.711Mu/ AAC/ G.726
1 Channel
2 Channel In
2 Channel Out
Supports
Supports
H.264: 24~ 10240Kbps , H.265: 14~ 6144Kbps
1 RS485
HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; SSL, IGMP, DHCP; DNS; DDNS; PPPOE; IPv4/ v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP, ONVIF (Profile S), PSIA, CGI



CP- UNC-BH21-VMD-V3

2 MP Network WDR Box Camera



Feature

Smart Detection

Ethernet

User Account

Smart Phone

Micro SD

Operating Temperature

Power Source

Power Consumption

Dimension

Weight

Specification

Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, People Counting, Heat Map

RJ-45 (100/1000Base-T)

20 Users

iPhone, iPad, Android Phone

Max 128GB

-30°C~+60°C , Less than 95%RH

DC12V, AC24V, PoE(802.3af)

<5.5W

161.6mm x 85.5mm x 74.0mm

0.72Kg