


# CP-UNC-TD20L4

2 MP Full HD IR Bullet Camera - 40Mtr.



## Main Features

- 1/2.8" 2Megapixel PS CMOS Image Sensor
- 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Smart Detection supported
- 3.6mm fixed lens (6mm optional)
- IR Range of 40 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-TD20L4

## 2 MP Full HD IR Bullet Camera - 40Mtr.

### Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Lens  
Gain Control(AGC)  
Back Light Compensation  
S/N Ratio  
Video Streaming  
Resolution  
Privacy Mask  
ICR  
Protocol  
Smart Detection  
Ethernet  
User Account  
IR  
Smart Phone  
Operating Temperature  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

### Specification

1/2.8" 2Megapixel progressive scan CMOS  
0.01Lux/F2.0(Color), 0Lux/F2.0(IR on)  
Auto/Manual, 1/3(4)~1/10000s  
Auto/Manual  
3.6mm(6mm optional)  
Auto/Manual  
BLC / HLC / DWDR  
More than 50dB  
Main Stream: 1080P/720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1~13/4fps)  
1080P(1920× 1080)/ 720P(1280× 720) / D1(704× 576/704× 480)/ CIF(352× 288/352× 240)  
Up to 4 areas  
Auto(ICR)/Color/B/W  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI  
Tripwire, Intrusion, Scene Change, Face detect  
RJ-45 (10/100Base-T)  
20 Users  
IR Range of 40 Mtr.  
iPhone, iPad, Android, Windows Phone  
-40°C~+60°C, Less than 95% RH  
DC12V, PoE (802.3af)  
Max 5W  
IP67  
70mm × 70mm × 180mm  
0.4kg(0.528kg with packaging)