

CP- UNC-TD20L4-D

2 MP Full HD WDR IR Bullet Camera - 40Mtr.



Main Features

- 1/2.7" 2Megapixel PS CMOS Image Sensor
- Max 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Smart Detection supported
- 3.6mm fixed lens (6mm optional)
- IR Range of 40 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TD20L4-D

2 MP Full HD WDR IR Bullet Camera - 40Mtr.

Feature

Image Sensor

Minimum Illumination

Shutter Speed

White Balance

Lens

Gain Control(AGC)

Back Light Compensation

S/N Ratio

Video Streaming

Resolution

Privacy Mask

ICR

Protocol

Smart Detection

Ethernet

User Account

IR

Smart Phone

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

1/2.7" 2Megapixel progressive scan CMOS

0.01Lux/F2.0(Color), 0Lux/F2.0(IR on)

Auto/Manual, 1/3(4)~1/10000s

Auto/Manual

3.6mm(6mm optional)

Auto/Manual

BLC / HLC / WDR

More than 50dB

Main Stream: 1080P/720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1~13/4fps)

1080P(1920× 1080) / 720P(1280× 720) / D1(704× 576/704× 480) / CIF(352× 288/352× 240)

Up to 4 areas

Auto(ICR)/Color/B/W

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI

Tripwire, Intrusion, Scene Change, Face detect, Abandoned/Missing, Audio detect

RJ-45 (10/100Base-T)

20 Users

IR Range of 40 Mtr.

iPhone, iPad, Android, Windows Phone

-30°C~+60°C, Less than 95% RH

DC12V, PoE (802.3af)

Max 6.5W

IP67

70mm × 70mm × 180mm

0.4kg(0.528kg with packaging)