

CP-UNC-TE20FL10-M

2 MP Full HD IP IR Bullet Camera - 100 Mtr.



Main Features

- 1/2.8" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 100 Mtrs.
- 3.3mm~12mm varifocal lens (7mm~22mm optional)
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-TE20FL10-M

2 MP Full HD IP IR Bullet Camera - 100 Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control(AGC)
 S/N Ratio
 Back Light Compensation
 Video Compression
 Video Streaming
 Video Output
 Resolution
 Privacy Mask
 ICR
 Audio Input
 Audio Compression
 Audio Output
 Alarm IN
 Alarm Out

 Protocol

 Ethernet
 User Account
 IR
 Smart Phone
 Micro SD
 Operating Temperature
 Power Source
 Power Consumption
 Weatherproof Standard
 Regulatory

Specification

1/2.8" 2Megapixel CMOS
 0.01Lux/F1.4 (Color), 0Lux/F1.4(IR on)
 Auto/Manual, 1/3(4)~1/10000s
 Auto
 3.3mm~12mm varifocal lens (7mm~22mm optional)
 Auto/Manual
 More than 50 dB
 BLC / HLC / DWDR
 H.264/ H.264H/ MJPEG
 Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
 1 channel BNC(1.0Vp-p, 75Ω)
 1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 1 Ch.
 G.711a/ G.711u/ PCM
 1 Ch.
 2 Ch.
 1 Ch.

 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S

 RJ-45 (10/100Base-T)
 20 users
 IR Range of 100 Mtr.
 iPhone, iPad, Android, Windows Phone
 Micro SD, Max 64GB
 -30°C~+60°C, Less than 95% RH
 DC12V, PoE(802.3af)
 <16W
 IP66
 CE, FCC and RoHS



*Product casing and specifications are subject to change without prior notice

CP- UNC-TE20FL10-M

2 MP Full HD IP IR Bullet Camera - 100 Mtr.

Feature

Dimension

Weight

Specification

288.3mm × 118.3mm × 101mm

2.5kg