

# CP- UNC-TE20L5-M

2 MP Full HD IP IR Bullet Camera - 50 Mtr.



## Main Features

- 1/2.8" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 3.6mm fixed lens (6mm,8mm optional)
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



\*Product casing and specifications are subject to change without prior notice

# CP- UNC-TE20L5-M

## 2 MP Full HD IP IR Bullet Camera - 50 Mtr.

Feature	Specification
Image Sensor	1/2.8" 2 Megapixel CMOS
Minimum Illumination	0. 1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W);0Lux/F1.2(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
Lens	3.6mm fixed lens (6mm,8mm optional)
Gain Control(AGC)	Auto/Manual
Back Light Compensation	BLC / HLC / DWDR
S/N Ratio	More than 50 dB
Video Compression	H.264/MJPEG
Video Streaming	Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
Video Output	1 channel BNC(1.0Vp-p, 75Ω)
Privacy Mask	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Audio Input	1 Ch.
Audio Output	1 Ch.
Audio Compression	G.711a/ G.711u/ PCM
Alarm IN	2 Ch.
Alarm Out	1 Ch.
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
Ethernet	RJ-45 (10/100Base-T)
User Account	20 users
IR	IR Range of 50 Mtr.
Smart Phone	iPhone, iPad, Android, Windows Phone
Micro SD	Micro SD, Max 32GB
Operating Temperature	-20°C~+60°C, Less than 90% RH
Power Source	DC12V, PoE(802.3af)
Power Consumption	<8W
Weatherproof Standard	IP66
Regulatory	CE, FCC and RoHS
Dimension	88mm × 76mm × 200.2mm
Weight	0.92kg