

CP- UNC-TH20ZL5-MD

2 MP WDR IR Bullet Camera - 50Mtr.



Main Features

- 1/1.9" 2MP PS CMOS Image Sensor
- Max 50/60fps@1080P
- Support H.264,MJPEG dual codec
- Ultra WDR(120dB), Ultra Defog, ROI, EIS, Smart detection, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 4 -8mm Motorized Lens
- IR Range of 50 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TH20ZL5-MD

2 MP WDR IR Bullet Camera - 50Mtr.

Feature	Specification
Image Sensor	1/1.9" 2MP Progressive scan CMOS
Minimum Illumination	0.002Lux/F1.65 (Color),0Lux/F1.65(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto/Manual
Gain Control(AGC)	Auto/Manual
Lens	4-8 mm Motorized Lens
S/N Ratio	More than 50dB
Back Light Compensation	BLC/ HLC/ WDR(120dB)
Video Compression	H.264/MJPEG
Video Streaming	Main Stream:1080P/720P(1 ~ 50/60fps), Extra Stream: D1/CIF(1 ~ 50/60fps), Third Stream: 1080P/720P/D1(1 ~ 25/30fps)
Resolution	1080P(1920× 1080) / 720P(1280× 720) /D1(704× 576) /CIF(352× 288)
Video Output	1 Port
Privacy Mask	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Audio Input	1 Channel
Audio Output	1 Channel
Audio Compression	G.711a / G.711u
Alarm IN	1 Channel In
Alarm Out	1 Channel Out
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI
Smart Detection	Tripwire, Intrusion, Scene Change, Missing/Abandoned, Audio detect, Face detect
Ethernet	RJ-45 (10/100Base-T)
User Account	20 Users
Smart Phone	iPhone, iPad, Android, Windows Phone
IR	IR Range of 50 Mtr.
Micro SD	Max 64GB
Operating Temperature	-30°C~+60°C, Less than 95% RH
Power Source	DC12V(AC24V optional), PoE (802.3af)
Power Consumption	Max 12.5W

CP- UNC-TH20ZL5-MD

2 MP WDR IR Bullet Camera - 50Mtr.

Feature

Weatherproof Standard

Dimension

Weight

Specification

IP66

272.90mm × 94.8mm × 94.8mm

1.25 Kg.