

CP- UNC-VE20ZL5-MD

2 MP Full HD WDR IP IR Vandal Dome Camera - 50 Mtr.



Main Features

- 1/2.7" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- WDR(120dB), Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 2.7mm ~12mm motorized lens
- Supports PoE, IP67, IK10, Micro SD Card
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-VE20ZL5-MD

2 MP Full HD WDR IP IR Vandal Dome Camera - 50 Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Gain Control(AGC)
 Lens
 S/N Ratio
 Back Light Compensation
 Video Compression
 Video Streaming
 Resolution
 Privacy Mask
 ICR
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 Protocol
 Smart Detection
 Ethernet
 User Account
 IR
 Smart Phone
 Micro SD
 Operating Temperature
 Power Source
 Power Consumption
 Weatherproof Standard
 Regulatory
 Dimension
 Weight

Specification

1/2.7" 2 Megapixel CMOS
 0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)
 Auto/Manual, 1/3(4)~1/10000s
 Auto/Manual
 Auto/Manual
 2.7mm~12mm Motorized
 More than 50 dB
 BLC / HLC / WDR(120dB)
 H.264/MJPEG
 Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
 1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 1 Ch.
 1 Ch.
 G.711a/ G.711u/ AAC
 1 Ch.
 1 Ch.
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
 Tripwire, Intrusion, Scene Change, Face Detect
 RJ-45 (10/100Base-T)
 20 users
 IR Range of 50 Mtr.
 iPhone, iPad, Android, Windows Phone
 Micro SD, Max 128GB
 -40°C~+60°C, Less than 95% RH
 DC12V, PoE(802.3af)
 <10W (with IR on, motorized lens working)
 IP67 & IK10
 CE, FCC and RoHS
 Ø159mm × 117.9mm
 0.8kg