

CP- VNC-D21R3

2 MP Full HD Array Dome Camera - 30Mtr.

INDIGO



Main Features

- 1/2.7" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- H.265, H.264, MJPEG Triple-stream Encoding
- DWDR, Day/Night (ICR), Corridor mode, 2D/3D-DNR, ROI, AWB, AGC, BLC
- 2.8mm lens (4mm optional)
- IR Range of 30 Mtrs, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



Instastream

CE FCC RoHS COMPLIANT

*Product casing and specifications are subject to change without prior notice

CP- VNC-D21R3

2 MP Full HD Array Dome Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control (AGC)
Lens
S/N Ratio
Video Compression
Video Streaming
Resolution
Frame Rate
Privacy Mask
ICR
WDR
Protocol
Ethernet
OSD
IR
Operating Temperature
Humidity
Power Source
Power Consumption
Dimension
Weight

Specification

1/2.7" 2MP Progressive scan CMOS
Colour: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR
Auto/Manual, 1/6~1/100000 s
Auto/Manual
Auto/Manual
2.8mm (4mm Optional)
>52dB
H.265, H.264, MJPEG
Triple
1920x1080
1080P (1920x1080): Max. 30 fps , 720P (1280x720): Max. 30 fps , D1 (720x576): Max. 8 fps
Up to 8 areas
IR-cut filter with auto switch (ICR)
DWDR
IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, ONVIF,API
10M/100M Base-TX Ethernet
Up to 8 OSDs
IR Range of 30 Mtr.
-35°C ~ +60°C (-31°F ~ 140°F)
≤ 95% RH (non-condensing)
12 V DC, or PoE (IEEE802.3 af)
Max 5.0W
Φ118 x 96 mm (Ø4.6" x 3.8")
0.2 kg