

# CP- VNC-T21FR5-VM

2 MP Full HD Array Bullet Camera - 50Mtr.

INDIGO



## Main Features

- 1/2.9" 2MP PS CMOS Image Sensor
- 1080P: Max. 30 fps , 720P: Max. 30 fps , D1: Max. 8 fps
- H.265, H.264, MJPEG Triple-stream Encoding
- Day/Night (ICR), Corridor mode, 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8~12 mm Varifocal Lens
- IR Range of 50 Mtrs, IP67, SD Card, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FCC RoHS COMPLIANT

# CP- VNC-T21FR5-VM

2 MP Full HD Array Bullet Camera - 50Mtr.



## Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control(AGC)  
 Video Compression  
 S/N Ratio  
 Video Streaming  
 Resolution  
 Frame Rate  
 Privacy Mask  
 ICR  
 ROI  
 Audio Input  
 Audio Output  
 Audio Compression  
 Alarm IN  
 Alarm Out  
 Protocol  
 Smart Detection  
 Ethernet  
 IR  
 OSD  
 Micro SD  
 Audio  
 Operating Temperature  
 Humidity  
 Power Source  
 Power Consumption

## Specification

1/2.9" 2MP Progressive scan CMOS  
 Colour: 0.06 Lux (F1.4, AGC ON) 0 Lux with IR  
 Auto/Manual, 1/6~1/100000s  
 Auto/Manual  
 2.8~12 mm Varifocal Lens  
 Auto/Manual  
 H.265, H.264, MJPEG  
 >52dB  
 Triple  
 1920x1080  
 1080P (1920 x 1080): Max. 30 fps , 720P (1280 x 720): Max. 30 fps , D1 (720 x 576): Max.8 fps  
 Up to 8 areas  
 IR-cut filter with auto switch (ICR)  
 Supports  
 impedance 35 kΩ; amplitude 2 V [p-p]  
 impedance 600 Ω; amplitude 2 V [p-p]  
 G.711  
 1 channel  
 1 channel  
 IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, ONVIF, API  
 Intrusion, crossing line, Motion detection, Audio detection, Face detection, Defocus, Scene Change, People counting  
 1 RJ45 10M/100M Base-TX Ethernet  
 Array Range of 50 Mtr.  
 Up to 8 OSDs  
 Micro SD, up to 128 GB  
 Two-way audio Supported  
 -35°C ~ +60°C (-31°F ~ 140°F)  
 ≤ 95% RH (non-condensing)  
 12 V DC, or PoE (IEEE802.3 af)  
 Max 8W



\*Product casing and specifications are subject to change without prior notice

# CP- VNC-T21FR5-VM

2 MP Full HD Array Bullet Camera - 50Mtr.



## Feature

Weatherproof Standard

Dimension

Weight

## Specification

IP67

253.4mm x 86mm x 71.7 mm (9.98" x 3.4" x 2.8")

0.58kg