

CP- VNC-T21ZR10-VMD

2MP WDR Array Bullet Camera - 100Mtr.

INDIGO



Main Features

- 1/2.8" 2MP PS CMOS Image Sensor
- Max 25/30fps@1080P
- H.265, H.264, MJPEG Triple-stream encoding
- WDR(120dB), Day/Night (ICR), Corridor mode, ROI, AWB, AGC, BLC, HLC
- 4.7 ~ 47mm Motorized Lens
- IR Range of 100 Mtrs, Micro SD, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FCC RoHS COMPLIANT

*Product casing and specifications are subject to change without prior notice

CP- VNC-T21ZR10-VMD

2MP WDR Array Bullet Camera - 100Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Video Compression
S/N Ratio
Video Streaming
Resolution
Video Output
Frame Rate
Privacy Mask
ICR
ROI
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
WDR
Protocol
Smart Detection
Ethernet
IR
OSD
Interface Ports
Micro SD
Audio
Operating Temperature
Humidity

Specification

1/2.8" 2MP Progressive scan CMOS
Colour: 0.002 Lux (F1.6, AGC ON) 0 Lux with IR
Auto/Manual, 1/10~1/100,000s
Auto/Manual
4.7 ~ 47mm Motorized Lens
Auto/Manual
H.265, H.264, MJPEG
>52dB
Triple
2MP (1920 × 1080)
1 BNC, impedance 75Ω; amplitude 1 V [p-p]
1080P (1920 x 1080): Max. 30 fps , 720P (1280 x 720): Max. 30 fps , D1 (720 x 576): Max. 30 fps
Up to 8 areas
IR-cut filter with auto switch (ICR)
Supports
impedance 35 kΩ; amplitude 2 V [p-p]
impedance 600Ω; amplitude 2 V [p-p]
G.711
2 Ch. IN
1 Ch. Out
WDR (120dB)
IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x, ONVIF, API
Intrusion, crossing line, Motion detection, Audio detection, Face detection, People counting
1 RJ45 10M/100M Base-TX Ethernet
IR Range of 100 Mtr.
Up to 8 OSDs
1 RS485
Micro SD, Up to 128 GB
Two-way audio Supported
-40°C ~ +60°C (-40°F ~ 140°F)
≤ 95% RH (non-condensing)



CP- VNC-T21ZR10-VMD

2MP WDR Array Bullet Camera - 100Mtr.



Feature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

DC12V±25%, AC24V±25% or PoE (IEEE802.3 at)

13.7W

IP67

305.5mm x 104.1mm x 97.3mm (12.0" x 4.1" x 3.8")

1.65 kg