

# CP-UNC-VD4K08L2

4K Full HD IR Vandal Dome Camera - 20Mtr.



## Main Features

- 1/2.3" 4K PS CMOS Image Sensor
- 7fps@4K
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 4mm fixed lens
- IR Range of 20 Mtrs, IP66, IK10, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP- UNC-VD4K08L2

## 4K Full HD IR Vandal Dome Camera - 20Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control(AGC)  
 Back Light Compensation  
 S/N Ratio

Video Streaming

Resolution

Privacy Mask  
 ICR

Protocol

Smart Detection

Ethernet

User Account

IR

Smart Phone

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

### Specification

1/2.3" 4K progressive scan CMOS

0.1Lux/F1.6 (Color), 0Lux/F1.6(IR on)

Auto/Manual, 1/3(4)~1/10000s

Auto/Manual

4mm

Auto/Manual

BLC / HLC / DWDR

More than 50dB

Main Stream: 4K(1~7fps)/3M/1080P/ (1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps),

4K(3840× 2160)3M(2048× 1536)/1080P(1920× 1080) /720P(1280× 720) /D1(704× 576/704× 480) / CIF(352× 288/352× 240)

Up to 4 areas

Auto(ICR)/Color/B/W

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

Tripwire, Intrusion, Scene Change, Face detect

RJ-45 (10/100Base-T)

20 Users

IR Range of 20 Mtr.

iPhone, iPad, Android, Windows Phone

-40°C~+60°C, Less than 95% RH

DC12V, PoE (802.3af)

Max 7W

IP66 & IK10

Φ110mm × 81mm

406g(531.8g with packaging)