

CP- ENC-T41L3-D

4 MP Full HD IP WDR IR Bullet Camera - 30 Mtr.



Main Features

- 1/3" 4 MP CMOS Image Sensor
- 25fps @4 MP
- H.265 Video Compression
- WDR(100dB), Day/Night (ICR), AWB, AGC, BLC
- 3.6mm (6mm optional) Lens
- IR Range of 30 Mtrs, IP66
- Mobile Software: RMOB
- CMS Software: RVMS



*Product casing and specifications are subject to change without prior notice

CP- ENC-T41L3-D

4 MP Full HD IP WDR IR Bullet Camera - 30 Mtr.



Feature

Image Sensor
Minimum Illumination
White Balance
Gain Control (AGC)
Lens
Back Light Compensation
Video Compression
Video Streaming
Resolution
Frame Rate
ICR
WDR
Protocol
Smart Detection
Ethernet
IR
Operating Temperature
Power Source
Weatherproof Standard
Dimension
Weight

Specification

1/3" 4 MP CMOS Image Sensor
0.01Lux@F1.2(Color)/0.001Lux@F1.2(B/W)
Auto/Manual
Auto/Manual
3.6mm (6mm optional) lens
Auto/Manual
H.265
Dual-stream
4M(2560x1440) / 3M(2048x 1536)/1080P(1920x 1080) / 720P(1280x 720) /D1(704x 576) / CIF(352x 288)
Main Stream: 4MP@25fps, Sub-Stream: D1
Supports
WDR(100dB)
ONVIF Support (profile S)
Tripwire, Intrusion, SceneChange, Abandoned/MissingObject
1 RJ45 10M/100M adaptive Ethernet port
IR Range of 30 Mtr.
-20°C~+65°C
DC12V±10%, PoE
IP66
59mm x 62.5mm x 210mm
430g