

CP- ENC-T41L3-VMD

4 MP Full HD IP WDR IR Bullet Camera - 30 Mtr.



Main Features

- 1/3" 4 MP CMOS Image Sensor
- 25fps @4 MP
- H.265 Video Compression
- WDR(100dB), Day/Night (ICR), AWB, AGC, BLC
- 3.6mm (6mm optional) Lens
- IR Range of 30 Mtrs, IP66, SD Card
- Mobile Software: RMOB
- CMS Software: RVMS



*Product casing and specifications are subject to change without prior notice

CP- ENC-T41L3-VMD

4 MP Full HD IP WDR IR Bullet Camera - 30 Mtr.



Feature

Image Sensor
Minimum Illumination
White Balance
Gain Control (AGC)
Lens
Video Compression
Back Light Compensation
Video Streaming
Resolution
Frame Rate
ICR
Audio Input
Audio Output
Alarm IN
Alarm Out
WDR
Protocol
Smart Detection
Ethernet
IR
Micro SD
Operating Temperature
Power Source
Weatherproof Standard
Dimension
Weight

Specification

1/3" 4 MP CMOS Image Sensor
0.01Lux@F1.2(Color)/0.001Lux@F1.2(B/W)
Auto/Manual
Auto/Manual
3.6mm (6mm optional) lens
H.265
Auto/Manual
Dual-stream
4M(2560x1440) / 3M(2048x 1536)/1080P(1920x 1080) / 720P(1280x 720) /D1(704x 576) /
CIF(352x 288)
Main Stream: 4MP@25fps, Sub-Stream: D1
Supports
1 Channel
1 Channel
2 Channel
1 Channel
WDR(100dB)
ONVIF Support (profile S)
Tripwire, Intrusion, SceneChange, Abandoned/MissingObject
1 RJ45 10M/100M adaptive Ethernet port
IR Range of 30 Mtr.
SD Card Max 128GB
-20°C~+65°C
DC12V±10%, PoE
IP66
59mm x 62.5mm x 210mm
430g