

# CP- ENC-T41L8-VMD

4 MP Full HD WDR IR Bullet Camera - 80 Mtr.



## Main Features

- 1/3" 4 MP CMOS Image Sensor
- 25fps @4 MP
- H.265/ H.264 Video Compression
- WDR(100dB), Day/Night (ICR), AWB, AGC, BLC
- 3.6mm (6mm optional) Lens
- IR Range of 80 Mtrs, IP66, SD Card
- Mobile Software: RMOB
- CMS Software: RVMS



\*Product casing and specifications are subject to change without prior notice

# CP- ENC-T41L8-VMD

4 MP Full HD WDR IR Bullet Camera - 80 Mtr.



## Feature

Image Sensor  
Minimum Illumination  
White Balance  
Gain Control (AGC)  
Lens  
Video Compression  
Back Light Compensation  
Video Streaming  
Resolution  
Frame Rate  
ICR  
Audio Input  
Audio Output  
Alarm IN  
Alarm Out  
WDR  
Protocol  
Ethernet  
IR  
Micro SD  
Operating Temperature  
Power Source  
Weatherproof Standard  
Dimension  
Weight

## Specification

1/3" 4 MP CMOS Image Sensor  
0.01Lux@F1.2(Color)/0.001Lux@F1.2(B/W)  
Auto/Manual  
Auto/Manual  
3.6mm (6mm optional) lens  
H.265/ H.264  
Auto/Manual  
Dual-stream  
4M(2560x1440) / 3M(2048x 1536)/1080P(1920x 1080) / 720P(1280x 720) /D1(704x 576) / CIF(352x 288)  
Main Stream: 4MP@25fps, Sub-Stream: D1  
Supports  
1 Channel  
1 Channel  
2 Channel  
1 Channel  
WDR(100dB)  
ONVIF Support (profile S)  
1 RJ45 10M/100M adaptive Ethernet port  
IR Range of 80 Mtr.  
SD Card Max 128GB  
-20°C~+65°C  
DC12V±10% , PoE  
IP66  
161.2mm x 97.45mm x 87.3mm  
891g