

CP-UNC-DA40L3-V3

4 MP Full HD Network Dome Camera - 30Mtr.



Main Features

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4M(2688×1520) and 25/30fps@3M(2304×1296)
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 2.8mm fixed lens (3.6mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-DA40L3-V3

4 MP Full HD Network Dome Camera - 30Mtr.



Feature

Image Sensor

Effective Pixels

Minimum Illumination

Shutter Speed

White Balance

Gain Control(AGC)

Lens

Back Light Compensation

S/N Ratio

Video Compression

Video Streaming

Resolution

Privacy Mask

ICR

Bit Rate

Protocol

Ethernet

User Account

Smart Phone

IR

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

1/3" 4MP Progressive scan CMOS

2688(H) x 1520(V)

0.1Lux/F2.0(Color), 0Lux/F2.0(IR on)

Auto/Manual, 1/3(4)s~1/100000s

Auto/Manual

Auto/Manual

2.8mm (3.6mm optional)

BLC/ HLC/ DWDR

More than 50dB

H.264/H.264H/ H.264B/MJPEG

Main Stream: 4M(1 ~ 20fps)/3M(1 ~ 25/30fps) , Sub Stream: D1(1 ~ 25/30fps)

4M(2688x1520)/3M(2304x1296)/1080P(1920x1080)/720P(1280x720)/ D1
(704x576/704x480) /CIF(352x288/352x240)

Up to 4 areas

Auto (ICR)/Color/B/W

H.264: 32kbps~8192kbps

IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS ONVIF, CGI

RJ-45 (10/100Base-T)

20 Users

iPhone, iPad, Android Phone

IR Range of 30 Mtr.

-30°C~+60°C , Less than 95%RH

DC12V, PoE (802.3af)

<4.3W (IR on)

IP67

Φ108mm x 84mm

0.25Kg (with package 0.38Kg)