


CP- UNC-DD40L3-D

4 MP Full HD WDR IR Dome Camera - 30Mtr.



Main Features

- 1/3" 4Megapixel PS CMOS Image Sensor
- 20fps@4MP, 25/30fps@3MP
- H.264 and MJPEG dual-stream encoding
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 3.6mm fixed lens (2.8mm, 6mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-DD40L3-D

4 MP Full HD WDR IR Dome Camera - 30Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control(AGC)
 Back Light Compensation
 S/N Ratio
 Video Compression
 Video Streaming
 Resolution
 Privacy Mask
 ICR
 Protocol
 Smart Detection
 Ethernet
 User Account
 Smart Phone
 IR
 Operating Temperature
 Power Source
 Power Consumption
 Weatherproof Standard
 Dimension
 Weight

Specification

1/3" 4Megapixel progressive scan CMOS
 0.01Lux/F2.1(Color), 0Lux/F2.1(IR on)
 Auto/Manual, 1/3(4)~1/10000s
 Auto/Manual
 3.6mm(2.8mm, 6mm optional)
 Auto/Manual
 BLC / HLC / WDR(120dB)
 More than 50dB
 N/A
 Main Stream: 4M(1~20fps)/3M(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1-5/8fps) (WDR on), 720P(1-18/2fps) (WDR off)
 4M(2560× 1440)/3M(2304× 1296)/1080P(1920× 1080)/720P(1280×720)/D1(704× 576/704× 480) /CIF(352× 288/352× 240)
 Up to 4 areas
 Auto(ICR)/Color/B/W
 IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI
 Tripwire, Intrusion, Scene Change, Face detect
 RJ-45 (10/100Base-T)
 20 Users
 iPhone, iPad, Android, Windows Phone
 IR Range of 30 Mtr.
 -40°C~+60°C, Less than 95% RH
 DC12V, PoE (802.3af)
 Max 5W
 IP67
 Ø108mm×84mm
 0.25Kg(with package 0.38Kg)