


CP- UNC-TA40L3**4 MP Full HD IP IR Bullet Camera - 30Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4MP, 25/30fps@3MP
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 2.8mm fixed lens (3.6mm optional)
- IR Range of 30 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TA40L3**4 MP Full HD IP IR Bullet Camera - 30Mtr.****Feature**

Image Sensor

Minimum Illumination

Shutter Speed

White Balance

Gain Control(AGC)

Lens

Back Light Compensation

S/N Ratio

Video Compression

Video Streaming

Resolution

Privacy Mask

Protocol

Ethernet

User Account

Smart Phone

IR

Ingress Protection

Operating Temperature

Power Source

Power Consumption

Dimension

Weight

Specification

1/3" 4MP Progressive scan CMOS

0.1Lux/F2.0(Color), 0Lux/F2.0(IR on)

Auto/Manual, 1/3(4)~1/10000s

Auto/Manual

Auto/Manual

2.8mm(3.6mm optional)

BLC/ HLC/ DWDR

More than 50dB

H.264/ H.264H/ H.264B/ MJPEG

Main Stream: 4M(1 ~ 20fps)/3M(1 ~ 25/30fps), Sub Stream D1(1 ~ 25/30fps)

4M(2688×1520)/3M(2304×1296)/1080P(1920×1080)/720P(1280×720)/ D1
(704×576/704×480) /CIF(352×288/352×240)

Up to 4 areas

IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,
PPPOE, DDNS, FTP, IP Filter, QoS

RJ-45 (10/100Base-T)

20 Users

iPhone, iPad, Android, Windows Phone

IR Range of 30 Mtr.

IP67

-30°C~+60°C , Less than 95%RH

DC12V, PoE (802.3af)

<4.3W(IR on)

Φ70mm × 165mm

0.38Kg(with package 0.44 Kg)