

# CP- UNC-TB40ZL6-MD

4 MP Full HD IR Bullet Camera - 60Mtr.



## Main Features

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4M and 25/30fps@3M
- H.264 and MJPEG dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC
- 2.7~12mm motorized lens
- IR Range of 60 Mtrs, IP67, PoE, SD Card
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



\*Product casing and specifications are subject to change without prior notice

# CP- UNC-TB40ZL6-MD

## 4 MP Full HD IR Bullet Camera - 60Mtr.



### Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Lens  
Gain Control (AGC)  
Video Compression  
S/N Ratio  
Back Light Compensation  
Video Streaming  
Resolution  
Privacy Mask  
ICR  
WDR  
Protocol  
Ethernet  
User Account  
IR  
Smart Phone  
Micro SD  
Operating Temperature  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

### Specification

1/3" 4MP Progressive scan CMOS  
0. 1Lux/F1.4 (Color), 0Lux/F1.4(IR on)  
Auto/Manual, 1/3(4)~1/100000s  
Auto/Manual  
2.7mm~12mm motorized Lens  
Auto/Manual  
H.264/ H.264H/ H.264B/ MJPEG  
More than 50dB  
BLC/ HLC/ WDR(120dB)  
Main Stream: 4M(1~20fps)/3M(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)  
4M(2688×1520)/4M(2560×1440)/3M(2304×1296)/1080P(1920×1080)/720P(1280×720)/D1  
(704×576/704×480)/CIF(352×288/352×240)  
Up to 4 areas  
Auto (ICR)/Color/B/W  
Supports  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP,  
DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF, PSIA, CGI  
RJ-45 (10/100Base-T)  
20 Users  
IR Range of 60 Mtr.  
iPhone, iPad, Android Phone  
SD, Max 128GB  
-30°C~+60°C , Less than 95%RH  
DC12V, PoE (802.3at)  
<12.5W  
IP67  
72mm× 80mm× 212.8mm  
0.65kg