

CP- VNC-D41R3-D

4 MP Full HD WDR Array Dome Camera - 30Mtr.

INDIGO



Main Features

- 1/3" 4MP PS CMOS Image Sensor
- 4MP (2592×1520): Max.20 fps; 4MP (2560×1440): Max.25 fps
- H.265, H.264, MJPEG Triple-stream Encoding
- WDR, Day/Night (ICR), Corridor mode, 2D/3D-DNR, AWB, AGC, BLC
- 2.8mm lens (3.6mm optional)
- IR Range of 30 Mtrs, Smart IR, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FC RoHS COMPLIANT

*Product casing and specifications are subject to change without prior notice

CP- VNC-D41R3-D

4 MP Full HD WDR Array Dome Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control (AGC)
Lens
Video Compression
Video Streaming
Resolution
Frame Rate
Motion detection
Privacy Mask
ICR
WDR
Protocol
Ethernet
OSD
IR
Operating Temperature
Humidity
Power Source
Power Consumption
Dimension
Weight

Specification

1/3" 4MP Progressive scan CMOS
Colour: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR
Auto/Manual, 1/6~1/100000 s
Auto/Manual
Auto/Manual
2.8mm (3.6mm Optional)
H.265, H.264, MJPEG
Triple
2592 x1520
4MP (2592x1520): Max.20 fps; 4MP (2560x1440): Max.25 fps, 3MP (2048x1520): Max.30 fps;
1080P (1920x1080): Max. 30 fps
Up to 2 areas
Up to 8 areas
IR-cut filter with auto switch (ICR)
Supports
IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP,
UPnP, HTTP, HTTPS, SMTP, 802.1x, ONVIF,API
10M/100M Base-TX Ethernet
Up to 8 OSDs
IR Range of 30 Mtr., Smart IR
-35°C ~ +60°C (-31°F ~ 140°F)
≤ 95% RH (non-condensing)
12 V DC, or PoE (IEEE802.3 af)
Max 5.0W
Φ118 x 96 mm (Ø4.6" x 3.8")
0.2 kg