

CP- VNC-T41FR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.

INDIGO



Main Features

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4MP
- H.265, H.264, MJPEG Triple-stream encoding
- WDR(120dB), Day/Night (ICR), Corridor mode, 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Varifocal Lens
- IR Range of 30 Mtrs, Smart IR, Micro SD, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FCC RoHS COMPLIANT

*Product casing and specifications are subject to change without prior notice

CP- VNC-T41FR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.



Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Video Compression
 S/N Ratio
 Video Streaming
 Resolution
 Frame Rate
 Privacy Mask
 ICR
 ROI
 Audio Input
 Audio Output
 Audio Compression
 Alarm IN
 Alarm Out
 WDR
 Protocol
 Smart Detection
 Ethernet
 IR
 OSD
 Micro SD
 Audio
 Operating Temperature

Specification

1/3" 4MP Progressive scan CMOS
 Colour: 0.02 Lux (F1.4, AGC ON), 0 Lux with IR on
 Auto/Manual, 1/6~1/100000 s
 Auto/Manual
 2.8~12mm Varifocal Lens
 Auto/Manual
 H.265, H.264, MJPEG
 >55dB
 Triple
 2592 × 1520
 4MP (2592×1520): Max. 20 fps; 4MP (2560×1440): Max. 25 fps, 3MP (2048×1520): Max. 30 fps; 1080P (1920×1080): Max. 30 fps
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Supports
 impedance 35 kΩ; amplitude 2 V [p-p]
 impedance 600 Ω; amplitude 2 V [p-p]
 G.711
 1 Ch. IN
 1 Ch. Out
 Optical WDR (Upto 120dB)
 IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x, ONVIF, API
 Intrusion, crossing line, Motion detection, Audio detection, Face detection, Defocus, Scene Change, People counting
 1 RJ45 10M/100M Base-TX Ethernet
 IR Range of 30 Mtr., Smart IR
 Up to 8 OSDs
 Up to 128 GB
 Two-way audio Supported
 -35°C ~ +60°C (-31°F ~ 140°F)



*Product casing and specifications are subject to change without prior notice

CP- VNC-T41FR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.



Feature

Humidity

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

≤ 95% RH (non-condensing)

12 V DC, or PoE (IEEE802.3 af)

max.8 W

IP67

253.4mm x 86mm x 71.7 mm (9.98" x 3.4" x 2.8")

0.58kg