

CP- VNC-T41ZR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.

INDIGO



Main Features

- 1/3" 4MP PS CMOS Image Sensor
- Max 20fps@4MP
- H.265, H.264, MJPEG Triple-stream encoding
- WDR(120dB), Day/Night (ICR), Corridor mode, 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Motorized Lens
- IR Range of 30 Mtrs, Micro SD, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FC RoHS COMPLIANT

*Product casing and specifications are subject to change without prior notice

CP- VNC-T41ZR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Video Compression
S/N Ratio
Video Streaming
Resolution
Frame Rate
Privacy Mask
ICR
ROI
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
WDR
Protocol
Smart Detection
Ethernet
IR
OSD
Micro SD
Audio
Operating Temperature
Humidity

Specification

1/3" 4MP Progressive scan CMOS
Colour: 0.02 Lux (F1.4, AGC ON), 0 Lux with IR on
Auto/Manual, 1/6~1/100000 s
Auto/Manual
2.8~12mm Motorized Lens
Auto/Manual
H.265, H.264, MJPEG
>55dB
Triple
2592 × 1520
4MP (2592×1520): Max. 20 fps; 4MP (2560×1440): Max. 25 fps, 3MP (2048×1520): Max. 30 fps; 1080P (1920×1080): Max. 30 fps
Up to 8 areas
IR-cut filter with auto switch (ICR)
Supports
impedance 35 kΩ; amplitude 2 V [p-p]
impedance 600 Ω; amplitude 2 V [p-p]
G.711
1 Ch. IN
1 Ch. Out
Optical WDR (Upto 120dB)
IPv4, IGMP, ICMP, ARP, TCP, UDP, L2TP,DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SIP, 802.1x, ONVIF, API
Intrusion, crossing line, Motion detection, Audio detection, Face detection, Defocus, Scene Change, People counting
1 RJ45 10M/100M Base-TX Ethernet
IR Range of 30 Mtr.
Up to 8 OSDs
Up to 128 GB
Two-way audio Supported
-35°C ~ +60°C (-31°F ~ 140°F)
≤ 95% RH (non-condensing)



*Product casing and specifications are subject to change without prior notice

CP- VNC-T41ZR3-VMD

4 MP WDR Array Bullet Camera - 30Mtr.



Feature

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

12 V DC, or PoE (IEEE802.3 af)

max.9 W

IP67

253.4 × 86 × 71.7 mm (9.98" × 3.4" × 2.8")

0.93 kg