

CP- UNC-TE51ZL5-MD

5MP Full HD WDR IR Bullet Camera - 50Mtr.



Main Features

- 1/3" 5MP PS CMOS Image Sensor
- Max 25fps @ 5MP
- H.265 / H.264 / MJPEG triple-stream encoding
- WDR(120dB), Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.7 -12mm Motorized Lens
- IR Range of 50 Mtrs, Micro SD, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



*Product casing and specifications are subject to change without prior notice

CP- UNC-TE51ZL5-MD

5MP Full HD WDR IR Bullet Camera - 50Mtr.



Feature	Specification
Image Sensor	1/3" 5MP Progressive scan CMOS
Minimum Illumination	0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)
Shutter Speed	Auto/Manual, 1/3(4)~1/10000s
White Balance	Auto
Gain Control(AGC)	Auto/Manual
Lens	2.7 -12mm Motorized Lens
Back Light Compensation	BLC/ HLC/ WDR(120dB)
S/N Ratio	More than 50dB
Video Compression	H.265/H.264/H.264H/H.264B/MJPEG
Video Streaming	Main Stream: 5M(1~25/30fps) / 1080P/720P(1~25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
Resolution	5M(2536×1920) / 3M(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)
Privacy Mask	Up to 4 areas
ICR	Auto(ICR)/Color/B/W
Audio Input	1 Channel
Audio Compression	G.711a / G.711u/ AAC
Audio Output	1 Channel
Alarm IN	2 Channel
Alarm Out	1 Channel
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI
Smart Detection	Tripwire, Intrusion, Scene Change, Missing/Abandoned, Audio detect, Face detect
Ethernet	RJ-45 (10/100Base-T)
User Account	20 Users
IR	IR Range of 50 Mtr.
Smart Phone	iPhone, iPad, Android, Windows Phone
Micro SD	Micro SD, Max 128GB
Operating Temperature	-30°C~+60°C, Less than 95% RH
Power Source	DC12V, PoE (802.3af)
Power Consumption	<11.5W (with IR on, motorized lens working)
Weatherproof Standard	IP67
Dimension	272.9 mm × 94.9mm × 94.9mm



*Product casing and specifications are subject to change without prior notice

CP- UNC-TE51ZL5-MD

5MP Full HD WDR IR Bullet Camera - 50Mtr.



Feature	Specification
Weight	1.1kg