

# CP- UNR-4K6128R8

## 128 Ch. H.264 4K Super Network Video Recorder



### Main Features

- Up to 128 channel IP camera input
- Up to 12Mp resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0), 1 eSATA port
- Support iSCSI to expand storage space
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/6/10/50/60
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, Wcmob
- CMS Software: KVMS, KVMS Pro



# CP- UNR-4K6128R8

## 128 Ch. H.264 4K Super Network Video Recorder

### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Hard Disk  
 Smart Phone  
 Trigger Events  
 HDD Management  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports  
 Record Interval  
 Max User Account  
 Ethernet  
 Protocols  
 Power Supply

### Specification

Dual-core embedded processor  
 128 channel  
 Embedded LINUX  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 2 HDMI(up to 3840× 2160), 1 VGA  
 H.264H / H.264 / MJPEG  
 3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768  
 Max 256 Mbps  
 The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16  
 MD Zones: 396(22×18).  
 Supports  
 Supports  
 16ch, low level effective, green terminal interface  
 8ch, Relay contact(1A@24VDC), NO/NC programmable, green terminal interface  
 8 SATA III ports, up to 48TB, 1 eSATA port  
 iPhone, iPad, Android, Windows Phone  
 Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips  
 Single, Raid 0/1/5/6/10/50/60 (Support global HDD hot-spares)  
 Manual, Schedule(Regular(Continuous), MD(Video detection: Motion detection,Camera blank, Video loss), Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
 128Mbps in Raid 5 mode, 64Mbps in single HDD mode  
 USB Device/Network/Internal SATA burner/eSATA Device  
 2 HDMI, 1 VGA, 4 USB ports(3 USB2.0, 1 USB3.0), 1 RS485, 1 RS232, 2 RJ45  
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
 128 users  
 2 RJ-45 port (10/100M/1000M), 2 Ethernet ports joint working or 2 independent 1000Mbps Ethernet ports  
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,PPPOE, DDNS, FTP, Alarm Server,ONVIF Version 2.4  
 AC110V~240V, 50~60Hz



\*Product casing and specifications are subject to change without prior notice

# CP- UNR-4K6128R8

## 128 Ch. H.264 4K Super Network Video Recorder

### Feature

Power Consumption

Working Temp

Dimensions

Weight

### Specification

40W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

486mm × 454.9mm × 91mm

<9kg (without HDD)