

CP- VNR-5F128

128 Ch. 4K Network Video Recorder



Main Features

- 128 Channel IP Camera Input
- H.265/H.264 dual Video Formats
- 512Mbps Incoming Bandwidth/ 384Mbps Outgoing Bandwidth
- Support 4K Resolution Upto 12MP Recording
- Support 16 SATA Ports up to 8TB each, 1 eSATA Port, 2 miniSAS Ports, 4 USB
- Support RAID 0/1/5/6/10/50/60, Redundant power supply
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



*Product casing and specifications are subject to change without prior notice

CP- VNR-5F128

128 Ch. 4K Network Video Recorder



Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface

Video Output

Compression

Video Resolution

Video Recording

Audio Input

Audio Output

Alarm Input

Alarm Output

Hard Disk

RAID

Playback

Interface Ports

Max User Account

Ethernet

Protocols

Power Supply

Power Output

Power Consumption

Working Temp

Working Humidity

Dimensions

Weight

Specification

Dual-core embedded processor

128 channel

Embedded LINUX

1 channel, BNC

GUI

2 HDMI, 1 VGA, 4K (3840x2160) @60Hz, 4K (3840x2160) @30Hz, 1920x1080p @60Hz, 1920x1080p @50Hz, 1600x1200 @60Hz, 1280x1024 @60Hz, 1280x720 @60Hz, 1024x768 @60Hz

H.265 /H.264

Upto 12MP, 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

512Mbps

1 channel

1 channel

24 Ch

8 Ch

16 SATA ports, Up to 8 TB Each

RAID 0/1/5/6/10/50/60

16 Channel

4 USB Port, 1 RS232, 1 RS485, 1 eSATA, 2 miniSAS port, Hot-Swap

128

4 RJ-45 10M/100M/1000M adaptive Ethernet Interface, 2 1000M SFP Ethernet Interface

HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP, ONVIF, Server, P2P

100 ~ 240V AC (Redundant power supply)

12V

≤ 50 W

-10°C ~ + 55°C (+14°F ~ +131°F)

10% ~ 90%

131mm x 482mm x 477mm

≤ 10 Kg