

CP- UNR-204T1-P4V2

4 Ch. 4PoE Network Video Recorder





Main Features

- H.264 Plus /H.264 codec decoding
- Up to 6Mp resolution preview & playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 6TB, 2 USB2.0, 4PoE Ports
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















CP- UNR-204T1-P4V2

4 Ch. 4PoE Network Video Recorder



Feature

Specification

Processor

Dual-core embedded processor

Operating System

IP Camera Input

Embedded LINUX

T.... T. II.

4 channel

Two-way Talk

1 channel Input, 1 channel Output, RCA

User Interface

GUI

Video Output

1 HDMI, 1 VGA H.264+/H.264

Compression
Video Resolution

1920×1080, 1280×1024, 1280×720, 1024×768

Video Recording

Max 80 Mbps, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 1.3Mp, 720P & etc.

Video Display Split

1/4

Motion Detection

MD Zones: 396(22×18).

Camera Blank

Supports

Hard Disk

1 SATA ports, up to 6TB

Smart Phone

iPhone, iPad, Android Phone

Trigger Events

Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips

Recording Mode

Manual, Schedule (Regular (Continuous), MD), Stop

Search Mode

Time /Date, MD and Exact Search (accurate to second)

Playback

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode

USB Device/Network

Record Interval

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Max User Account

128 users

Interface Ports

1 HDMI, 1 VGA, 2 USB(1 RearUSB2.0, 1 FrontUSB2.0), 1 RJ45

Ethernet

1 RJ-45 port (10/100Mbps), 1 Independent 100Mbps Ethernet Port, 4 ports (IEEE802.3at/af)

Protocols

 ${\sf HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search, ONVIF 2.4, and the property of the proper$

CGI Conformant

Power Supply
Power Consumption

Single, DC48V/1.25A <4W (without HDD)

Working Temp

-10 ~+55°C / 10~90%RH / 86~106kpa

Dimensions

260mm x 224.9mm x 47.6mm

Weight

0.8kg (without HDD)



