

CP- UNR-204T1-V2

4 Ch. Network Video Recorder



Main Features

- Up to 4ch@1080P Real-time Live-view & Playback
- H.264Plus /H.264/MJPEG dual codec decoding
- Up to 6Mp resolution preview & playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 6TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP-UNR-204T1-V2

4 Ch. Network Video Recorder



Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode

 Playback

 Backup Mode
 Interface Ports
 Record Interval
 Max User Account
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp
 Dimensions

Specification

Dual-core embedded processor
 4 channel
 Embedded LINUX
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 Smart H.264+/H.264/MJPEG
 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Max 80 Mbps, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 1.3Mp, 720P & etc.
 1/4
 MD Zones: 396(22×18).
 Supports
 Supports
 iPhone, iPad, Android Phone
 1 SATA III ports, up to 6TB
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen Tips
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second)

 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

 USB Device / Network
 1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users
 1 RJ-45 port (10/100Mbps)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
 DC12V/2A
 <4W (without HDD)
 -10 ~+55°C / 10~90%RH / 86~106kpa
 260mm x 224.9mm x 47.6mm



*Product casing and specifications are subject to change without prior notice

CP- UNR-204T1-V2

4 Ch. Network Video Recorder



Feature	Specification
Weight	0.8Kg (without HDD)