

# CP- UNR-404T1

## 4 Ch. Network Video Recorder



### Main Features

- 4 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 80Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-404T1

## 4 Ch. Network Video Recorder

### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 Recording Mode  
 Search Mode

### Specification

Dual-core embedded processor  
 4 channel  
 Embedded LINUX  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 1 HDMI, 1 VGA  
 H.264 / MJPEG  
 2560×1920, 2048×1536, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768  
 Max 80 Mbps  
 1/4  
 MD Zones: 396(22×18).  
 Supports  
 Supports  
 iPhone, iPad, Android, Windows Phone  
 1 SATA ports, up to 4TB  
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen  
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Playback  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode  
 USB Device / Internal SATA burner/ Network

Record Interval  
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Max User Account  
 128 users

Interface Ports  
 1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45

Ethernet  
 1 RJ-45 port (10/100M/1000M)

Protocols  
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3

Power Supply  
 DC12V/2A

Power Consumption  
 10W(without HDD)

Working Temp  
 -10 ~+55°C / 10~90%RH / 86~106kpa

Dimensions  
 325mm × 240mm × 45mm

# CP- UNR-404T1

## 4 Ch. Network Video Recorder

Feature	Specification
Weight	1.25 Kg (without HDD)