

CP- UNR-404T2

4 Ch. Network Video Recorder



Main Features

- 4 Ch. with 1080p Realtime Live View
- H.264+ and H.264 dual codec decoding
- Up to 5Mp resolution preview & playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UNR-404T2

4 Ch. Network Video Recorder



Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Max User Account
Record Interval
Interface Ports
Ethernet
Protocols
Power Supply

Specification

Dual-core embedded processor
Embedded LINUX
4 channel
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
H.264+/H.264/MJPEG
1920 × 1080 , 1280 × 1024, 1280 × 720 , 1024 × 768
Max 200 Mbps , 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.
1/4
MD Zones: 396(22×18).
Supports
Supports
4 Channel, Low Level Effective, Green Terminal Interface
2 Channel, NO/NC Programmable, Green Terminal Interface
2 SATA III Ports, up to 8TB
iPhone, iPad, Android Phone
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Camera Blank, Video Loss), Alarm, Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / Network
128 users
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
1 HDMI, 1 VGA, 2 USB(1 USB 2.0, 1 USB 3.0), 1 RS485, 1 RS232, 1 RJ45
1 RJ-45 port (10/100M/1000M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
DC12V/4A



CP- UNR-404T2

4 Ch. Network Video Recorder



Feature

Power Consumption

Working Temp

Dimensions

Weight

Specification

<20W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 285.8mm x 56mm

1.6kg (without HDD)