

# CP- UNR-7064T16-R

## 64 Ch. Network Video Recorder



### Main Features

- 64Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 256Mbps incoming bandwidth
- Support 16 SATA HDDs up to 64TB, 1 eSATA up to 16TB, 4 USB2.0
- Support RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



\*Product casing and specifications are subject to change without prior notice

# CP- UNR-7064T16-R

## 64 Ch. Network Video Recorder

### Feature

Processor  
 Operating System  
 IP Camera Input  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Smart Phone  
 Hard Disk  
 Trigger Events  
 RAID  
 Recording Mode  
 Search Mode

### Specification

Dual-core embedded processor  
 Embedded LINUX  
 64 channel  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 2 HDMI, 1 VGA, 1 TV  
 H.264 / MJPEG  
 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768 & etc.  
 Max 192 Mbps  
 1/4/8/9/16/25/36  
 MD Zones: 396(22x18).  
 Supports  
 Supports  
 16 channel  
 6 channel  
 iPhone, iPad, Android, Windows Phone  
 16 SATA ports up to 64TB, 1 eSATA port  
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen  
 Raid 0/1/5/6/10  
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Playback

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode

USB Device / eSATA Device / Internal SATA burner/ Network

Interface Ports

2 HDMI, 1 VGA, 1TV, 4 USB2.0, 1 RS485, 1 RS232, 2 RJ45

Max User Account

20 users

Record Interval

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Ethernet

2 RJ-45 port (10/100M/1000M)

Protocols

HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2

Power Supply

AC 100~240V, 50/60 Hz



# CP- UNR-7064T16-R

## 64 Ch. Network Video Recorder

### Feature

Power Consumption

Working Temp

Dimensions

Weight

### Specification

75W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

448mm × 490mm × 133mm

10.5kg~11.5kg (without HDD)