

# CP- VNR-5F64

## 64 Ch. 4K Network Video Recorder



### Main Features

- 64 Channel IP Camera Input
- H.265/H.264 dual Video Formats
- 384 Mbps Incoming/Outgoing Bandwidth
- Support 4K Resolution Upto 12MP Recording
- Support 16 SATA Ports up to 8TB each, 1 eSATA Port, 2 miniSAS Ports, 4 USB
- Support RAID 0/1/5/6/10/50/60, Redundant power supply
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



*\*Product casing and specifications are subject to change without prior notice*

# CP- VNR-5F64

## 64 Ch. 4K Network Video Recorder



### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface

Video Output

Compression  
Video Resolution  
Video Recording  
Video Display Split

Audio Input  
Audio Output  
Alarm Input  
Alarm Output

Hard Disk  
RAID

Playback

Interface Ports  
Max User Account

Ethernet

Protocols

Power Supply  
Power Output  
Power Consumption  
Working Temp

Working Humidity

Dimensions

Weight

### Specification

Dual-core embedded processor

64 channel

Embedded LINUX

1 channel, BNC

GUI

2 HDMI, 1 VGA, 4K (3840x2160) @60Hz, 4K (3840x2160) @30Hz, 1920x1080p @60Hz, 1920x1080p @50Hz, 1600x1200 @60Hz, 1280x1024 @60Hz, 1280x720 @60Hz, 1024x768 @60Hz

H.265 /H.264

Upto 12MP, 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF

384Mbps

1/4/8/9/16/25/36

1 channel

1 channel

24 Ch

8 Ch

16 SATA ports, Up to 8 TB Each

RAID 0/1/5/6/10/50/60

16 Channel

4 USB Port, 1 RS232, 1 RS485, 1 eSATA, 2 miniSAS port, Hot-Swap

128

4 RJ-45 10M/100M/1000M adaptive Ethernet Interface, 2 1000M SFP Ethernet Interface

HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP, ONVIF, Server, P2P

100 ~ 240V AC (Redundant power supply)

12V

≤ 50 W

-10°C ~ + 55°C ( +14°F ~ +131°F )

10% ~ 90%

131mm x 482mm x 477mm

≤ 10 Kg