

# CP- UNR-108F1

8 Ch. Network Video Recorder



## Main Features

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 56Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras, Support P2P (QR code Scan)
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



*\*Product casing and specifications are subject to change without prior notice*

# CP- UNR-108F1

## 8 Ch. Network Video Recorder



### Feature

Processor  
IP Camera Input  
Operating System  
User Interface  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Motion Detection  
Video Loss  
Camera Blank  
Smart Phone  
Hard Disk  
Trigger Events  
Recording Mode  
Search Mode  
Playback  
Backup Mode  
Interface Ports  
Record Interval  
Max User Account  
Ethernet  
Protocols  
Power Supply  
Power Consumption  
Working Temp  
Dimensions  
Weight

### Specification

Dual-core embedded processor  
8 channel  
Embedded LINUX  
GUI  
1 HDMI, 1 VGA  
H.264 / MJPEG  
1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768  
Max 56 Mbps  
1/4/8/9  
MD Zones: 396(22x18).  
Supports  
Supports  
iPhone, iPad, Android, Windows Phone  
1 SATA ports, up to 4TB  
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen  
Manual, Schedule (Regular (Continuous), MD, Alarm), Stop  
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom  
USB Device / Internal SATA burner/ Network  
1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45  
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec  
128 users  
1 RJ-45 port (10/100M)  
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4  
Single, DC5V/2A  
<2W (without HDD)  
-10 ~+55°C / 10~90%RH / 86~106kpa  
192mmx128mmx36mm  
320g (without HDD)



\*Product casing and specifications are subject to change without prior notice