

CP- UNR-208T2-V2

8 Ch. Network Video Recorder



Main Features

- Up to 8ch@1080P Real-time Live-view & Playback
- H.264Plus /H.264 dual codec decoding
- Up to 6Mp resolution preview & playback
- Max 80Mbps incoming bandwidth
- Support 2 SATA HDDs up to 12TB, 2 ports (1 RearUSB2.0, 1 FrontUSB2.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UNR-208T2-V2

8 Ch. Network Video Recorder



Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Interface Ports
 Record Interval
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp
 Dimensions
 Weight

Specification

Dual-core embedded processor
 8 channel
 Embedded LINUX
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 H.264+/H.264
 1920×1080, 1280×1024, 1280×720, 1024×768
 Max 80 Mbps, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 1.3Mp, 720P & etc.
 1/4/8/9
 MD Zones: 396(22×18).
 Supports
 Supports
 iPhone, iPad, Android Phone
 2 SATA III ports, up to 12TB
 Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
 Manual, Schedule(Regular(Continuous), MD, Stop
 Time /Date, MD and Exact Search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Network
 128 users
 1 HDMI, 1 VGA, 2 ports (1 RearUSB2.0, 1 FrontUSB2.0), 1 RJ45
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 RJ-45 port (10/100M) , 1 Independent 100Mbps Ethernet Port
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
 DC12V/4A
 <3W (without HDD)
 -10 ~+55°C / 10~90%RH / 86~106kpa
 375mm x 275mm x 53mm
 1.5kg (without HDD)



*Product casing and specifications are subject to change without prior notice