



8 Ch. H.265 4K Network Video Recorder





#### **Main Features**

- Up to 8 channel IP camera input
- H.265/H.264 dual codec decoding
- Up to 8Mp resolution preview and playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 12TB, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



















# CP- UNR-4K4082-V2

## 8 Ch. H.265 4K Network Video Recorder



**Feature** Specification

Processor Dual-core embedded processor

IP Camera Input 8 channel

Operating System Embedded LINUX

Two-way Talk 1 channel Input, 1 channel Output, RCA

User Interface GUI

Video Output 1 HDMI, 1 VGA
Compression H.265/H.264

Video Resolution 3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768

Video Recording 200 Mbps Video Display Split 1/4/8/9

Motion Detection MD Zones: 396(22×18).

Video Loss Supports
Camera Blank Supports

Alarm Input 4 Channel, Low Level Effective, Green Terminal Interface
Alarm Output 2 Channel, NO/NC Programmable, Green Terminal Interface

Smart Phone iPhone, iPad, Android Phone Hard Disk 2 SATA III ports, up to 12TB

Trigger Events Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips

Recording Mode Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tamper-

ing, Video Loss), Stop

Search Mode Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous

camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode USB Device/Network

Record Interval 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Interface Ports 1 HDMI, 1 VGA, 2 USB Ports(1 USB2.0, 1 USB3.0), 1 RJ45

Max User Account 128 users

Ethernet 1 RJ-45 port (10/100M/1000M), 1 Independent 1000Mbps Ethernet Port

Protocols HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,

PPPoE,DDNS, FTP, IP Search, ONVIF 2.4, CGI Conformant

Power Supply DC12V/4A







8 Ch. H.265 4K Network Video Recorder



## **Feature**

**Power Consumption** 

Working Temp

**Dimensions** 

Weight

## **Specification**

<6.9W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 281.5mm x 56mm

1.6kg (without HDD)



